

Product Name

Enviroskin Exterior 100% Acrylic Water Proofing Membrane

Product Description

Enviroskin Exterior 100% Acrylic Water Proofing Membrane is ultra premium flexible water proofing membrane.



Product benefit

Stretchable: Enviroskin is developed with new generation acrylic elastomeric binder that makes film flexible

Crack bridging: Enviroskin can bridge cracks happening due to minor structural movements and will not be visible from outside.

Water Repellent: Enviroskin is specially developed for water repellancy and water resistant properties to ensure protection against water seepage problems.

High Build up: Enviroskin is high volume and high viscosity product that build high DFT film on wall with unique high durable finish

Product features


Washability	Excellent
Available Packs	4 Lit, 10 Lit, 20 Lit
Sheen Variants	Semi-Gloss
Coverage	Coverage - 4-6 Sqm/lit/coat* *Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.
Colour Options	White & Pastal Shades

Areas of Application


The areas of application are all cementations surfaces and other construction materials (suitable for use on surfaces displaying hairline cracks or cracks up to 1mm width).

How to Apply


Pre Painting Steps



Previously painted surfaces: Treat mould or fungus with commercial bleaching agent.



Remove loose and flaking paint. Sand with 180-mesh sandpaper to reduce previous film to a dull finish or wash with sugar soap rinsing subsequently with copious quantities of water.



Touch up bare areas with Sureprep Interior/Exterior Acrylic Sealer Under coat or over the entire surface if it has patchy appearance.



Unpainted surfaces: After proper curing of the concrete, wash the surface with water. Allow complete drying of surface before painting.

Paint Application / System

Stir the contents thoroughly before use. On very hot days the product may be diluted with up to 5% Acrylic drying retarder for ease of application.

Fill cracks and imperfections with proprietary filler, sand back and spot prime. Follow with two full coats of finish.

No primer is required for sound concrete surfaces. Apply first coat of Enviroskin Water Proofing Membrane with 10% to 20% thinning followed by two thick coats.

Strip of old paint if it is a unsound painted concrete surfaces then apply first coat of Enviroskin Water Proofing Membrane with 10-29% thinning followed by two thick coats.

Drying Time



Touch Dry	30 Min
Recoating Time	3-4 hrs

Finish - Type / Category

Exterior - Ultra - Premium Water Proofing Membrane.

Additional Information

Gloss level @ 60°	Gloss - 65 - 75 Unit Semi Gloss - 25 - 35 Unit Low Sheen - 8 - 12 unit
Method of application	Brush, Roller and Spray
Flammability	Non Flammable
Safety Precautions	<ul style="list-style-type: none"> • Do not apply when surface temperature is below 10°C. • Provide adequate ventilation during use. • Keep out of reach of children. • Check cross cut adhesion of old paint before repainting. • In normal condition, a week's curing is required to develop full hardness & resistant properties. • Avoid exposure of new paint film to steam for 48 hours and to washing and scrubbing for 7 days.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

 <p>APCO BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited)</p>	<p>FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apccoatings.com</p>	<p>SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apccoatings.com</p>
--	---	---