

Ezicover Alkyd Undercoat

Ezicover alkyd undercoat is professional range oil based undercoat for interior and exterior application.

PRODUCT BENEFITS

Easy sanding

Good opacity

Good sealing and adhesion



PRODUCT FEATURES

AVAILABLE PACKS



COVERAGE



Coverage 12-14 sqm/ltr**

Actual coverage may vary from the quoted coverage due to factors such as method & condition of application and surface roughness and porosity.

AREAS OF APPLICATION



All timber and metal surfaces, plywood, masonry, gib-board and hardboard.

HOW TO APPLY

SURFACE PREPARATION

Remove all dirt, dust, grease and other contaminants. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill cracks and imperfections with a suitable filler and spot prime.

APPLICATION PROCESS

STEP 1

For sound painted surfaces apply one coat of Ezicover Alkyd undercoat followed by two coats of Ezicover gloss enamel. For unsound painted surfaces remove loose and flaking paint and apply one coat of Ezicover Alkyd undercoat finish with two coats of Ezicover gloss enamel.

STEP 2

For plyboard/hardboard and mesonite board apply one coat of Ezicover Alkyd undercoat and finish with two coats of Ezicover gloss enamel. For bare steel in good condition apply one coat of Ezicover Alkyd undercoat followed by two coats of Ezicover gloss enamel.

ADDITIONAL INFORMATION

DRYING TIME

TOUCH DRY



4
HOURS


Gloss level @ 60°:

Matt - 0 - 5 Unit

Method of application: Brush, Roller and Spray

Highly flammable, Dangerous goods class 3.2, Flash point 32°C UN 1263, PG III

RECOAT



+



16 hours
Recoat

SAFETY PRECAUTION

- > Do not apply when surface temperature is below 10 degree C.
- > Provide adequate ventilation during use.
- > Keep out of reach of children.
- > Check cross cut adhesion of old paint before repainting.
- > Under normal conditions a week's curing is required to develop full hardness & resistance properties.

SAFETY INFORMATION

- > If swallowed give water to dilute. Do not induce vomiting. Get medical attention.
- > EYES: Hold open and flush with running water for at least 15 minutes.
- > Skin: Remove contaminated clothes and wash skin thoroughly with soap and water.
- > Inhalation: Remove to fresh air. If any symptoms persist, seek prompt medical attention.
- > Do not pour left over paint down the drain or water courses.
- > In the event of spill, contain spillage with help of sand, dust or earth.
- > No Added lead, chromium or mercury compounds.
- > Left over paint disposal: Leftover paint/drums should not be disposed in soil/drains.

Consumers should consult a local recycling agency for proper disposal of paints/drums.

Thinner / Cleanup - Enamel Thinner