

Product Name

Decor Alkyd High Gloss Enamel

Product Description

Decor Alkyd High Gloss Enamel is professional quality high gloss alkyd based enamel.



Product benefit

Rich look: Decor Alkyd offers very smooth and glossy finish gives excellent look after painting.

Versatile application: Product is developed for multi use interior and exterior requirement. It can be applied on

concrete wall, wood, metal, boards with suitable primer.

Washable: Product has superior washability and most kind of stains can be wiped out easily.

Product features

Washability	High
Available Packs	1 Lit, 4 Lit, 10 Lit, 20 Lit
Finish	Very Smooth - Gloss
Coverage	Coverage - 14-16 Sqm/lit/coat* *Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.
Colour Options	APCO 1320 Colours and dark shades.

Areas of Application

The areas of application are interior and exterior primed timber, masonry and metal surfaces, ideal finish for doors, windows, wrought iron furniture, exterior trimmings and fittings.

How to Apply

Pre Painting Steps



Remove all dust, dirt and grease from the surface.



If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with anti-fungal solution.



Fill nail-holes cracks etc with suitable filler and sand smooth using 220-mesh sandpaper.




Apply suitable sealer or primer to prepare an even surface.

Paint Application / System

- Stir the contents thoroughly before and during use. Apply uniformly after proper surface preparation and suitable priming.
- For sound painted surfaces apply one coat of Decor Alkyd undercoat followed by two coats of Decor Alkyd Interior/Exterior Gloss Enamel.
- For bare cement render/brick and masonry apply one coat of Decor Alkyd undercoat followed by two coats of Decor Alkyd Interior/Exterior Gloss Enamel.
- For new timber and allied substrates apply Oilprep Interior/Exterior Wood Primer followed by one coat of Decor Alkyd undercoat. Finish with two coats of Decor Alkyd Interior/Exterior Gloss Enamel.
- For weathered galvanised iron and zinc alumina, apply Metalprep Interior/Exterior Galvo Enamel primer followed by two coats of Decor Alkyd Interior/Exterior Gloss Enamel.

Drying Time



Touch Dry	4hrs
Recoating Time	16hrs

Finish - Type / Category

Interior / Exterior Professional Enamel.


- For bare steel in good condition no primer is required, if required apply one coat of Metalprep Interior/Exterior Enamel Primer. Finish with two coats of Decor Alkyd Interior/Exterior Gloss Enamel.
- For bare steel in poor condition apply Metal Prep Interior/Exterior Enamel Primer followed by two coats of Decor Alkyd Interior/Exterior Gloss Enamel.

Additional Information

Gloss level @ 60°	Gloss - 85-95 Unit
Method of application	Brush, roller or spray. Please use the method best suited to your requirement and skill. Use of a synthetic or mohair sleeve of 5 mm nap is suggested on flat surfaces. For airless spray application, optimum pressure of 2200 psi and nozzle size of 0.011-0.013 inches is suggested as a guideline.
Flammability	Highly flammable, UN 1263, PG III
Safety Precautions	<ul style="list-style-type: none">• Do not apply when surface temperature is below 10°C.• Provide adequate ventilation during use.• Keep out of reach of children.• Check cross cut adhesion of old paint before repainting.• Under normal conditions a week's curing is required to develop full hardness & resistant properties.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

 APCO BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited)	FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apcocoatings.com	SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apcocoatings.com
---	--	--