

# Highshield Roof Acrylic Gloss

Highshield roof acrylic gloss is a premium quality finish for roofs and tiles. The product offers non-toxic film when fully dried.



## PRODUCT BENEFITS


- Long lasting film
- Excellent Dirt pick up resistance
- Colour retention

## PRODUCT FEATURES

### AVAILABLE PACKS




### COVERAGE



Coverage 12-14 sqm/ltr\*\*

Actual coverage may vary from the quoted coverage due to factors such as method & condition of application and surface roughness and porosity.

### AREAS OF APPLICATION



For all previously painted and unpainted roofs, fibre cement boards, exterior masonry substrate and tiles.

## HOW TO APPLY

### SURFACE PREPARATION

Before painting, remove dust, dirt and grease from the surface to be painted. If mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill nail holes, cracks etc with suitable proprietary filler and sand smooth using 180 - grit sandpaper. Light sanding using 220 - mesh sandpaper must be carried out on smooth surfaces after the application of sealers or undercoats to prepare an even substrate. Previously unpainted cement, concrete or bricks should be cleaned with a stiff brush. No Primer is needed. Instead apply three coats of Highshield Gloss Roof Acrylic finish with light sanding after the first coat.

### APPLICATION PROCESS

Stir the contents thoroughly before and during use. Apply uniformly direct from the container after proper surface preparation. For sound painted surfaces no primer is required. Apply two coats of Highshield Roof Acrylic gloss. For weathered galvanised iron and zinc alume apply Metalprep Galvo Enamel Primer followed by two coats of Highshield Roof Acrylic Gloss. For bare steel apply one coat of Metalprep Enamel Primer followed by two coats of Highshield Roof Acrylic Gloss.

## ADDITIONAL INFORMATION

### DRYING TIME

TOUCH DRY



30  
MINUTES

Gloss level @ 60°:

Gloss - 65 -75 unit

Method of application: Brush, Roller and Spray

### RECOAT



4 hours

## SAFETY PRECAUTION

---

- > Do not apply when surface temperature is below 10°C.
- > Provide adequate ventilation during use.
- > Keep out of reach of children.
- > Check cross cut adhesion of old paint before repainting.
- > Under normal conditions a week's curing is required to develop full hardness & resistance properties.

## SAFETY INFORMATION

---

- > If swallowed give water to dilute. Do not induce vomiting. Get medical attention.
- > EYES: Hold open and flush with running water for at least 15 minutes.
- > Skin: Remove contaminated clothes and wash skin thoroughly with soap and water.
- > Inhalation: Remove to fresh air. If any symptoms persist, seek prompt medical attention.
- > Thinner / Cleanup - Water. Though product is designed for undiluted application, it may be thinned up to 10% if necessary.