

Metalprep Galvo Enamel Primer

Metalprep galvo enamel primer is single pack primer based on alkyd resin and anticorrosive pigments. It is recommended for use on new and weathered galvanised iron and zinc alume.



PRODUCT BENEFITS

Good corrosion resistance:

Based on synthetic resins and contains corrosion inhibiting pigments.

PRODUCT FEATURES

AVAILABLE PACKS




COVERAGE



Coverage 12-14 sqm/ltr**

Actual coverage may vary from the quoted coverage due to factors such as method & condition of application and surface roughness and porosity. Colour options: Grey

AREAS OF APPLICATION



Galvanised iron, Zinc Alume

HOW TO APPLY

SURFACE PREPARATION

Remove all dust, dirt and grease from the surface. For previously unpainted galvanised iron surfaces - Sand the surface lightly to provide mechanical key to the primer. Wipe the surface clean. Allow complete drying. Rust spots if any on galvanised iron shall be cleaned thoroughly. The oxide layer on galvanised iron should be removed by a stiff nylon brush using plenty of fresh water.

APPLICATION PROCESS

STEP 1

Stir the contents thoroughly before and during use. Apply uniformly direct from the container after proper surface preparation.

STEP 2

For weathered galvanised iron and zinc alume, apply one coat of Metalprep Galvo Enamel Primer. Finish with two coats of desired roof coating.

ADDITIONAL INFORMATION

DRYING TIME

TOUCH DRY



30
MINUTES


Gloss level @ 60°:

Matt - 0 - 5 Unit

Method of application: Brush, Roller and Spray

Highly flammable, Dangerous goods class 3.2, Flash point 32°C UN 1263, PG III.

RECOAT



12 hours
Recoat

SAFETY PRECAUTION

- > Do not apply when surface temperature is below 10 degree C.
- > Provide adequate ventilation during use.
- > Keep out of reach of children.
- > Check cross cut adhesion of old paint before repainting.
- > Under normal conditions a week's curing is required to develop full hardness & resistance properties.

SAFETY INFORMATION

- > If swallowed give water to dilute. Do not induce vomiting. Get medical attention.
- > EYES: Hold open and flush with running water for at least 15 minutes.
- > Skin: Remove contaminated clothes and wash skin thoroughly with soap and water.
- > Inhalation: Remove to fresh air. If any symptoms persist, seek prompt medical attention.
- > Do not pour left over paint down the drain or water courses.
- > In the event of spill, contain spillage with help of sand, dust or earth.
- > No Added lead, chromium or mercury compounds.
- > Left over paint disposal: Leftover paint/drums should not be disposed in soil/drains.
Consumers should consult a local recycling agency for proper disposal of paints/drums.
Thinner / Cleanup - Enamel Thinner