

Product Name

Rapid Paint stripper

Product Description

It is non-caustic and effective paint removing gel suitable for easy removal of all enamels varnishes and lacquers.

Product benefit

Easy and quick Removal

Antisagg and uniform spreadable

Effective on various coatings

Product features

Available Packs	4L, 1L, 500 ML.
-----------------	-----------------

Areas of Application

To remove the old coatings from timber, metal and concrete surfaces. It is effective for two pack paint as well.

How to Apply

Pre Painting Steps



Wipe the surface clean. Loosely adhered paint shall be removed fully by mechanical means.

Paint Application / System

- Stir the content thoroughly. Apply uniformly by brush. Ensure that all the areas are covered with Paint stripper.
- Allow the paint stripper to remain for 10 minutes so as to soften the old paint. After 10 minutes, with the help of suitable scrapper remove the paint gently.
- It is recommended to wear safety gloves while using this product.

Finish - Type / Category Paint remover

• Repeat the above procedure if there is still some paint left on the surface. Wash the surface thoroughly.

Additional Information

Toxicity	Contains Methylene Chloride.
Flammability	Highly flammable, Dangerous goods clause 3.2 Flash point less than 10 degree Celsius UN1912 PG II.
Safety Precautions	 Avoid contact with skin. Keep away from heat and open flame. Keep out of reach of children. Refer to the material safety data sheet before using the product.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.



FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apcocoatings.com

SUVA OFFICE:

P.O. Box 4202, Samabula, Suva. FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apcocoatings.com