

Product Name

Apco Wood Putty

Product Description

Apco wood putty is flexible oil based filler for wooden surfaces for filling of dents and other surface imperfections. Deep dents should not be filled at a stretch but in thin layers .

Product benefit

No shrinkage

Very good adhesion

Good sandability

Very good levelling property

Product features

Available Packs	1 Lit, 4 Lit, 10 Lit, 20 Lit
Coverage	10 - 15 sq.ft/kg for upto 1.5 mm thickness in 2 coats
Colour Options	Off White

Areas of Application

Timber

How to Apply

Pre Painting Steps



Ensure that surface is free from loose dust and moisture.




Surface should be primed with suitable primer/ sealer for better bonding.

Paint Application / System

- Apply Apco wood putty with putty knife wherever necessary on primed wood surfaces such as dent, cracks, undulation etc.

Drying Time



Recoating Time

8-10 hrs

Finish - Type / Category

Filler

Additional Information

- Recommended only for wood.
- It is important to apply a coat of suitable Primer before filling with Apco wood putty.
- Do not apply when surface temperature is below 10° C.
- Provide adequate ventilation during use.
- Keep out of reach of children.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

 <p>APCO BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited)</p>	<p>FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apccoatings.com</p>	<p>SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apccoatings.com</p>
--	---	---