

Product Name

Timbercare Natural Oil Stain - Interior/Exterior

Product Description

Timbercare Natural Oil Stain - Interior/Exterior is an oleoresinous based timber stain formulated in light fast weather resistant colours. It highlights the aesthetic beauty of wood grains.



Product benefit

- Fungus and Insect resistant.
- Moisture regulating action.
- Protects timber for years.
- Excellent adhesion to various wood.
- Enhances wood grains in traditional colours.

Product features

| | |
|-----------------|---|
| Washability | High |
| Available Packs | 1 Lit, 4 Lit, 10 Lit, 20 Lit |
| Sheen Variants | Matt |
| Coverage | Coverage - 10-12 Sqm/lit/coat* *Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity. |
| Colour Options | Timbercare colour card |

Areas of Application

The areas of application are wooden houses, external claddings, roof underlays, windows, shutters, doors, fences and garden furniture.

How to Apply

Pre Painting Steps



Remove all dirt, dust, loose flaking paint if any using sandpaper. Always carry out sanding of wooden surfaces along the grain marks.



Sand the surface smooth using sandpaper and dust off.



Dust off entire area to be painted. Fills surface imperfections like nail-holes, cracks etc by suitable wood filler.

Paint Application / System

- Stir the contents thoroughly before and during use.
- No primer is required before application of this product.
- Apply two or three uniform coats by convenient method of application. Resist the temptation to apply this product at excessively high film thickness.

Drying Time



| | |
|----------------|-------|
| Touch Dry | 4hrs |
| Recoating Time | 16hrs |

Finish - Type / Category


Premium Natural Oil Stains.

Additional Information

| | |
|-----------------------|--|
| Gloss level @ 60° | Matt : <5% Units |
| Method of application | By brushing, spraying or application by rag. Please use the method best suited to your requirement and skill. The quality of finish may depend on type and colour of wood and it's absorption characteristics, apart from method of application. |
| Flammability | Highly flammable, UN 1263, PG III |
| Safety Precautions | <ul style="list-style-type: none">• Do not apply when surface temperature is below 10°C.• Provide adequate ventilation during use.• Keep out of reach of children.• Check cross cut adhesion of old paint before repainting.• Under normal conditions a week's curing is required to develop full hardness & resistant properties. |

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

| | | |
|--|---|---|
|  BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited) | FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apcocoatings.com | SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apcocoatings.com |
|--|---|---|