

Product Name

Timbercare Transtain Transparent Interior Stain

Product Description

Timbercare Transtain Transparent Interior Stain is high quality transparent wood stain for toning aesthetic beauty of wood grains. The product is designed for interior use. It can be top coated by most of the Timbercare clear wood finishes.



Product benefit

- Suitable for mass production.
- Unique shades.
- Enhances wood grains in traditional colours.
- Can be over coated with various finishes.

Product features

Available Packs	0.5 Lit, 4 Lit, 10 Lit, 20 Lit
Coverage	Coverage - 10-12 Sqm/lit/coat* *Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.
Colour Options	Transtain shade card

Areas of Application

The areas of application are dressed timber furniture, cabinets and panelling.

How to Apply

Pre Painting Steps



Ensure that the timber to be stained is clean and dry. Carry out sanding along the grain marks using fine sandpaper.



Sand the surface smooth using sandpaper and dust off.




Dust off entire area to be painted. Fills surface imperfections like nail-holes, cracks etc by suitable filler.

Paint Application / System

- Stir the contents thoroughly before and during use. Apply Transtain evenly using a soft cloth pad. Wipe-off excess stain immediately. Allow it to dry for 30 minutes. Wipe the stained area using cloth moistened with small quantity of mineral turps. Apply appropriate sealer coat.
- Transtain can also be applied by spray. Ensure application of a thin coat by passing the spray gun briskly over the area to be painted. Allow the stained surface to dry for 30 minutes.
- The choice of sealer coat depends on the selection of clear topcoat. For Timbercare Instant Drying Lacquer, use Instant Drying Sanding Sealer. In case of Timbercare Polyurethane Clear finishes, use Touchwood Brushable Sanding Sealer.

Drying Time



Touch Dry	5mins
Recoating Time	30mins

Finish - Type / Category

Premium Transparent Interior Stain.

Additional Information

Method of application	By spray or by using a soft rag along the grains. Please use the method best suited to your requirement and skill. The colour and appearance of stain largely depends on type and colour of wood and it's absorption characteristics, apart from application skill.
Flammability	Highly flammable, UN 1263, PG III
Safety Precautions	<ul style="list-style-type: none"> • Do not apply when surface temperature is below 10°C. • Provide adequate ventilation during use. • Keep out of reach of children. • Check cross cut adhesion of old paint before repainting. • Under normal conditions a week's curing is required to develop full hardness & resistant properties.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

 <p>APCO BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited)</p>	<p>FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apcocoatings.com</p>	<p>SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apcocoatings.com</p>
--	--	--