

Timbercare Transtain Transparent Stain

Transtain is high quality transparent wood stain for toning aesthetic beauty of wood grains. The product is designed for interior use. It can be topcoated by most of the timbercare clear wood finishes.



PRODUCT BENEFITS

- Unique shades
- Enhances natural wood look
- Easy application

PRODUCT FEATURES

AVAILABLE PACKS



COVERAGE



Coverage 10-12 sqm/ltr**

Actual coverage may vary from the quoted coverage due to factors such as method & condition of application and surface roughness and porosity.

AREAS OF APPLICATION



Wooden furnitures, cabinets and panelling

HOW TO APPLY

SURFACE PREPARATION

Ensure that timber to be painted is clean and dry. Carry out sanding along the grain marks using fine sand paper. Dust off entire area to be painted. Fill surface imperfections like nail holes and cracks etc by suitable filler. Sand smooth surface using fine sand paper and dust off.

APPLICATION PROCESS

Stir the contents thoroughly before and during use. Apply Transtain evenly using a soft cloth pad. Wipe-off excess stain immediately. Allow it to dry for 30 minutes. Wipe the stained area using cloth moistened with small quantity of mineral turps. Apply appropriate sealer coat. Transtain can also be applied by spray. Ensure application of a thin coat by passing the spray gun briskly over the area to be painted. Allow the stained surface to dry for 30 minutes. The choice of sealer coat depends on the selection of clear topcoat. For Timbercare Instant Drying Lacquer, use Instant Drying Sanding Sealer. In case of Timbercare Polyurethane Clear finishes, use Touchwood Brushable Sanding sealer.

Caution: Always carry out sanding of wooden surfaces along the grain marks. Same colour of transtain on different timbers could be different due to the fact that timber varies in colour, texture, absorption etc. Hence test it on a small area before commencing the job. Tufkote 342 over stained timber may lead to bleeding of certain stains hence use selected transtain colours.

ADDITIONAL INFORMATION

DRYING TIME

TOUCH DRY



5
MINUTES

RECOAT



30 minutes
Recoat

Method of application: Spray or ragging along the grains

Highly flammable, Dangerous goods class 3.2, Flash point 32°C, UN 1263, PG III. HAZCHEM 3(Y)E

SAFETY PRECAUTION

- > Do not apply when surface temperature is below 10°C.
- > Provide adequate ventilation during use.
- > Keep out of reach of children.
- > Check cross cut adhesion of old paint before repainting.
- > Under normal conditions a week's curing is required to develop full hardness & resistance properties.

SAFETY INFORMATION

- > If swallowed give water to dilute. Do not induce vomiting. Get medical attention.
- > EYES: Hold open and flush with running water for at least 15 minutes.
- > Skin: Remove contaminated clothes and wash skin thoroughly with soap and water.
- > Inhalation: Remove to fresh air. If any symptoms persist, seek prompt medical attention.
- > Thinner / Cleanup - Transtain reducer