

Timbercare Brushable Sanding Sealer

Brushable sanding sealer is a premium quality single pack polyurethane based clear sanding sealer for sealing of wood grains.

PRODUCT BENEFITS

- Fast dry
- Easy sanding
- Ideal grain sealer
- Excellent adhesion to various woods




PRODUCT FEATURES

AVAILABLE PACKS



COVERAGE



Coverage- 14-16 Sqm per lit per coat*

Actual coverage may vary from the quoted coverage due to factors such as method & condition of application and surface roughness and porosity.

AREAS OF APPLICATION



Dressed timber furniture, door, veneers, wall panelling etc.

HOW TO APPLY

SURFACE PREPARATION

Ensure that timber to be painted is clean and dry. Remove all wax, grease and oil by cleaning with thinner. Carry out sanding along the grain marks using fine sand paper. Dust off entire area to be painted. Fill surface imperfections like nail holes and cracks etc by suitable filler. Sand smooth surface using fine sand paper and dust off.

APPLICATION PROCESS

Stir the contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

On new surface, apply one or two coats of Brushable sanding sealer. Carry out light sanding after 24 hours to obtain smooth finish. Apply polyurethane crystal clear in desired finishes as topcoat. Transparent stains as desirable can be used prior to application of sealer coat.

Caution: Allow enough time before subjecting the sealer coat to sanding. Always carry out sanding of wooden surfaces along grain marks. Use only recommended thinner for dilution and clean up.

ADDITIONAL INFORMATION

DRYING TIME

TOUCH DRY



2
HOURS


Gloss @ 60°:

Matt - 0 - 5 units

Method of application: Spray only.

Highly flammable, Dangerous goods class 3.2, Flash point 32°C, UN 1263, PG III. HAZCHEM 3[Y]E

RECOAT



+



16 hours
Recoat

SAFETY PRECAUTION

- > Do not apply when surface temperature is below 10°C.
- > Provide adequate ventilation during use.
- > Keep out of reach of children.
- > Check cross cut adhesion of old paint before repainting.
- > Under normal conditions a week's curing is required to develop full hardness & resistance properties.

SAFETY INFORMATION

- > If swallowed give water to dilute. Do not induce vomiting. Get medical attention.
- > EYES: Hold open and flush with running water for at least 15 minutes.
- > Skin: Remove contaminated clothes and wash skin thoroughly with soap and water.
- > Inhalation: Remove to fresh air. If any symptoms persist, seek prompt medical attention.
- > Thinner / Cleanup - Thinner 600/Mineral turps. The product can be applied by brush without dilution.
However 5% thinner may be added if required. For spraying dilute up to 15% with thinner depending on climatic condition