

Product Name

Timbercare ID Lacquer Interior

Product Description

Timbercare ID Lacquer Interior is a high quality nitrocellulose based clear lacquer with fast drying characteristics.



Product benefit

- Instant dry.
- Excellent finish.
- Tough and wear resistant finish.
- Enhance wood look.

Product features

Washability	Excellent
Available Packs	1 Lit, 4 Lit, 10 Lit, 20 Lit
Sheen Variants	Gloss, Semi-Gloss and Matt
Coverage	Coverage - 10-12 Sqm/lit/coat* *Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.
Colour Options	Clear

Areas of Application

The areas of application are dressed timber furniture, doors, veneers, wall panelling etc. Ideal for furniture and cabinet manufacture in production line joineries.

How to Apply

Pre Painting Steps



Remove all wax, grease and other contaminants by cleaning with mineral turps.



Fill the surface imperfections like nail holes, cracks etc by suitable filler. Sand smooth the surface and dust off.



Sand the surface uniformly along the grain marks and dust off.

Paint Application / System

- Stir the contents thoroughly before and during use.
- On new surface apply one or two coats of Instant Drying Sanding Sealer by spray. Carry out light sanding after thorough drying and dust off the area. Apply two uniform coats of Instant Drying Lacquer in desired finishes.
- On previously applied surfaces, apply two uniform coats of Instant Drying Lacquer with minimum 30 minutes recoating interval.
- For toning of wood grains, Transtain can be used appropriately prior to application of Instant Drying Sanding Sealer.

Drying Time



Touch Dry	5mins
Recoating Time	30mins

Finish - Type / Category

Premium Interior Wood Finish.

Additional Information

Gloss level @ 60°	Gloss - > 85 units Semi gloss: 20-50 Units, Matt - < 10 units
Method of application	Spray only. The quality of finish may depend on type of wood and it's absorption characteristics apart from application skill.
Flammability	Highly flammable, UN 1263, PG III
Safety Precautions	<ul style="list-style-type: none">• Do not apply when surface temperature is below 10°C.• Provide adequate ventilation during use.• Keep out of reach of children.• Check cross cut adhesion of old paint before repainting.• Under normal conditions a week's curing is required to develop full hardness & resistant properties.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

 BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited)	FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apcocoatings.com	SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apcocoatings.com
---	--	--