

Product Name

Timbercare Deck and Furniture Oil Exterior

Product Description

Timbercare Deck and Furniture Oil Exterior is a tung oil enriched protective composition, that penetrates for effective and easy protection of timber decks and exterior furniture.



Product benefit

- Fungus and Mould resistant.
- Excellent water repellancy.
- Does not crack, peel or blister.
- Water Repellancy.
- Suitable for variety of wood.

Product features

Washability	High
Available Packs	1 Lit, 4 Lit, 10 Lit, 20 Lit
Coverage	Coverage - 8-10 Sqm/lit/coat* *Actual coverage may vary from the quoted coverage due to factors such as method and condition of application and surface roughness and porosity.
Colour Options	Clear (Slightly Yellowish)

Areas of Application

The areas of application are all timber decks, garden furniture etc.

How to Apply


Pre Painting Steps

Allow the timber to weather sufficiently. Treat the surface with anti-fungal solution and then clean with fresh water.

Paint application / System

- Stir the contents thoroughly before use. No primer is required while applying this product on timber.
- Apply one coat of decking oil and allow it to get soaked in to the timber. Wipe out excess oil after 2-4 hours by using soft cotton cloth.
- Apply second coat after 12 hours of drying. Wipe out excess oil after 2-4 hours. Generally two coats are sufficient. Do not over apply.
- Allow the timer to dry completely. The surface shall be free from all contaminants like oil, grease, wax and chemicals.

Drying Time



Touch Dry	30mins
Recoating Time	12hrs

Finish - Type / Category


Deck and Furniture Oil.

Additional Information

Method of application	Brushing is recommended. Foam roller can be used but require special application skills and it should be ensured that all the excess oil is brushed off.
Flammability	Highly flammable, UN 1263, PG III
Safety Precautions	<ul style="list-style-type: none">• Do not apply when surface temperature is below 10°C.• Provide adequate ventilation during use.• Keep out of reach of children.• Check cross cut adhesion of old paint before repainting.• Under normal conditions a week's curing is required to develop full hardness & resistant properties.

DISCLAIMER:

Although the facts and suggestions in this publication are based on our own research and are believed reliable, we cannot assume any responsibility for performance or results obtained through the use of our products herein described, nor do we accept any liability for loss or damages directly caused by our products. The user is held to check the quality, safety and all other properties of our product prior to use. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

 BRILLIANT PAINTS, BRILLIANT COLOURS (Division of Asian Paints (SP) Limited)	FACTORY: P.O. Box 694, Lautoka, FIJI. Ph: 679 6662799; Fax: 679 - 6663959 Email: contact.fiji@apcocoatings.com	SUVA OFFICE: P.O. Box 4202, Samabula, Suva, FIJI. Ph : (679) 3371267/68; Fax: (679) 3371269 Email: contact.fiji@apcocoatings.com
--	---	---